

AM SERIES

PUSH-AROUND VERTICAL LIFTS



Performance

Working Height		
25AM	31'	9.45 m
30AM	35.7'	10.88 m
38AM	44'	13.4 m
Platform Height		
25AM	24'10"	7.57 m
30AM	29.7'	9.05 m
38AM	38'	11.58 m
Platform Capacity		
25AM	350 lb	160 kg
30AM/38AM	300 lb	136 kg
Platform Size W x L		
25AM/30AM/38AM	29.5" x 25.5"	
Overall Height		
25AM/30AM	78"	1.98 m
38AM	103.9"	2.64 m
Overall Vehicle Width		
25AM	29.5"	.75 m
30AM/38AM	29.1"	.74 m
Overall Vehicle Length		
25AM	48"	1.22 m
30AM	51.9"	1.31 m
38AM	57.4"	1.46 m
Overall Vehicle Length Without Battery Pack		
25AM/30AM/38AM	47"	1.19 m
Overall Height - Tilted Back		
25AM/30AM	n/a	
38AM	77.5"	1.97 m
Overall Length - Tilted Back		
25AM/30AM	n/a	
38AM	119"	3.02 m
Ground Entry Height		
25AM/30AM/38AM	18.9"	.48 m
Outrigger Footprint Length		
25AM	68.1"	1.57 m
30AM	79"	2.00 m
38AM	85.8"	2.13 m
Outrigger Footprint Width		
25AM	61.8"	1.38 m
30AM	79"	2.00 m
38AM	83.3"	2.02 m
Distance to Wall - Front		
25AM	6"	15.5 cm
30AM	9.5"	24.13 cm
38AM	15"	38.1 cm
Distance to Wall - Side		
25AM	11.5"	28.9 cm
30AM	20.5"	52.07 cm
38AM	24"	61 cm
Weight		
25AM - AC/DC	825/905 lb	374/411 kg
30AM - AC/DC	1030/1110 lb	467/503 kg
38AM - AC/DC	1265/1395 lb	574/633 kg

The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



Standard Specifications

Wheels

Rear Drive Wheels	10 x 2 in.	25.4 x 5.1 cm
Front Caster Wheels	6 x 2 in.	15.2 x 5.1 cm

Standard Features

- Lanyard Attachment Anchor for Body Harness
- Quick-Change 26 in. W x 28 in. L (.66 x .71 m) —Gull-Wing Entry Platform
- Quick-Change Platform Mounts
- Low Maintenance Anodized Mast
- Non-Marking Tires
- 110 Volt Double Receptacle in Platform
- 93 AH Lead-Acid Battery—DC Models Only
- Descent Alarm
- Automatic Battery Charger—DC Models Only
- Battery Discharge Indicator (BDI)
- Hourmeter
- Roller Loading Device: For Loading on Pickup Trucks
- Auto Power Saver—Shuts Off Power When Idled
- ANSI, OSHA & CSA Compliant

Accessories & Options

- 22x22" Gullwing Platform
- 26x26" Ride Side Entry Platform
- Tool Tray
8 x 18 x 5 (20 x 46 x 13 cm)
- Programmable 4-Digit Security Lock
- Crane Hook
- Locking Casters
- Auxiliary Lowering



JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417

www.jlg.com

An Oshkosh Corporation Company

Part No.: 3132140
R1020_A92.20
Printed in USA